

FLEXCUT COMPARISON



PRODUCT	FlexCut® 35	FlexCut® 35 Air	FlexCut® 45	FlexCut® 65	FlexCut® 85	FlexCut® 105	FlexCut® 125
RECOMMENDED	6 mm	6 mm	16 mm	19 mm	25 mm	32 mm	38 mm
MAXIMUM	10 mm	10 mm	22 mm	25 mm	32 mm	38 mm	44 mm
SEVERANCE	13 mm	13 mm	25 mm	32 mm	38 mm	51 mm	57 mm
PIERCE THICKNESS	N/A	N/A	13 mm	16 mm	19 mm	22 mm	25 mm
GOUGING RATE	N/A	N/A	3.4 kg/hr	4.0 kg/hr	4.5 kg/hr	5.2 kg/hr	6.3 kg/hr
AIR SUPPLY TYPE	External	Internal or External	External	External	External	External	External
NET WEIGHT	12 kg	12 kg	15 kg	35 kg	35.5 kg	41 kg	41 kg
INPUT POWER	120/230/1/50/60	120/230/1/50/60	230-400/1-3/50/60	230-400/3/50/60	230-400/3/50/60	400/3/50/60	400/3/50/60
OUTPUT RANGE	15A-35A	15A-35A	15A-45A	20A-65A	25A-85A	30A-105A	30A-125A
HANDHELD DRAG CUTTING	•	•	•	•	•	•	•
GRID CUTTING	•	•	•	•	•	•	•
PLASMA GOUGING			•	•	•	•	•
MECHANIZED CUTTING			•	•	•	•	•
EXTENDED CUTTING			•	•	•	•	•
PRECISION CUTTING	•		•	•	•	•	•
MARKING			•	•	•	•	•
INCLUDES	Work Clamp & Cable, Shoulder Strap			Work Clamp & Cable			