

SPRINTER™ 180Si

STICK/PULSED TIG WELDER



Shown:
Sprinter 180Si, K5453-1

PORTABLE. VERSATILE. POWERFUL.

The Sprinter™ 180Si delivers **industrial-grade performance** in a compact, portable design. Weighing under 20 lbs., it's built to go wherever the job takes you—with the power to get it done.

With 180 amps of output, it easily handles electrodes up to 5/32", and features two dedicated stick modes for 7018 and 6010 for excellent arc performance.

More than just a stick welder, the Sprinter 180Si includes advanced TIG capabilities—including high-frequency start, pulsed TIG mode, and amptrol compatibility—making it a full-featured TIG solution in a lightweight package.

For easy operation, a simple, intuitive display allows for fast setup and easy adjustments—allowing you to easily dial in the right settings for whatever project comes your way.

Processes »

DC Stick, DC Touch-Start TIG, DC High Frequency TIG, DC Pulsed TIG

Applications »

Light Duty Fabrication, Maintenance, Farm, Auto Body, Aerospace, Light structural, Shipbuilding

Output »



Input »



Product Numbers »

K5453-1 Sprinter 180Si

K5585-2 Sprinter 180Si W/ Foot Pedal & Case

K5953-2 Sprinter 180Si W/ Hand Slide & Case

VALUE-ADDED FEATURES

- **Two Stick Modes** - Dedicated E6010 and E7108 weld modes allow for greater welding versatility and superior performance
- **Dual Input** - Automatically adjust to run off 120V or 230V
- **Adaptive Arc Force** - Helps minimize the electrode sticking in the weld puddle for improved ease-of-use
- **Automatic Hot Start** - Senses and adjusts the weld current during arc striking for easier and cleaner starting
- **High Frequency TIG** - Provides reliable arc starting without touching the tungsten to the workpiece
- **Pulsed TIG Mode** - Provides heat management and enhanced control on thinner materials
- **Automatic Post Flow** - Built-in post-flow control based on selected amperage to protect weld/tungsten from contamination
- **Industrial IP23 Protection** – Designed with high-impact resistant plastics to deliver reliable performance in challenging conditions

KEY CONTROLS



1. Carry Handle
2. Seven Segment Display
3. Weld Selection Button
4. Thermal Indicator
5. Voltage Reduction Device Indicator
6. Pulse Mode On/Off Button
7. Amperage Adjustment Knob
8. Twist Mate™ Receptacles
9. 8-Pin Receptacle

INTERFACE - WELD MODES / INDICATORS



Crisp Stick Mode - Tuned for cellulosic electrodes such as 6010/6013



Soft Stick Mode - Tuned for electrodes such as 7018



VRD - Indicates when automatic voltage reduction is active during non-welding periods



Pulse Rate - Indicates selected pulse frequency [0.1 - 100 pulses per second]



Hi Frequency TIG Mode - For use with remote control such as Hand Amptrols or Foot Pedal



Touch Start TIG Mode - For use to initiate arc by touch & lifting tungsten

Pulsed TIG – Precision and Control

The Sprinter™ 180Si delivers advanced Pulsed TIG capabilities for superior arc control – allowing for professional TIG performance without a large, high-end system.

Why Pulsed TIG?

- **Reduce Heat Distortion:** Controlled heat input minimizes warping and burn-through—especially on stainless steel and thin metals.
- **Cleaner Weld Appearance:** Controlled pulsing produces a tighter bead profile and improved aesthetics.
- **Increase Travel Speed:** Faster movement across the joint without sacrificing penetration or quality.
- **Better Control:** Ideal for precision work where consistency and finish are critical.

Sprinter Features:

- **Easy Pulse Adjustment** – Set pulse frequency [0.1 - 100 pulses per second] with a single button for quick, precise tuning.
- **Automatic Current Regulation** – When using an amptrol, the system automatically balances peak and background amperage for consistent heat control.

PULSED TIG PERFORMANCE



RECOMMENDED ACCESSORIES



Machine Carrying Case

Water resistant, lockable case designed with enough space to store the Sprinter 180Si welder and all of the TIG One-Pak accessories.

[Order K5549-1](#)



Welding Cart

Designed to store and transport a welder, gas cylinder, cables and accessories.

[Order K2275-1](#)



Foot Pedal

Pedal for TIG Welding

[Order K4361-1](#)



Caliber® 17/18/26 Series TIG Torch

Expendables Kit - 1/16"-1/8"

Includes all of the front end parts needed to run a Gas Lens setup on 17/18/26 Series TIG Torches.

[Order KP4760-HD](#)



Gas Regulator with Hose

Compensated flowmeter regulator shielding gas kit for use with Argon (Ar).

[Order 3100211](#)



Caliber® 17 Series TIG Torch - Flexible, 12.5 ft.

Premium Caliber® TIG Torch with a Flexible Torch Head and a 150A 60% Duty Cycle.

[Order K4841-17F-1 and K1622-7](#)



Linear Slide Hand Amptrol

Optional for HF TIG operation to initiate the arc and control welding current

[Order K5924-1](#)



Rotary Hand Amptrol

Optional for HF TIG operation to initiate the arc and control welding current

[Order K963-5](#)



Arc Start Switch

Optional for TIG operation to initiate arc without Amptrol.

[Order: K814](#)



Image
Coming
Soon

8 Pin to 6 Pin Adapter

Adapt machine to work with 6 pin accessories

[Buy as K5685-1](#)

PACKAGES AVAILABLE



K5453-1 Sprinter™ 180Si Base Model

- Sprinter 180Si welder
- Insulated Electrode Holder and Cable
- Heavy Duty Work Clamp and Cable
- 230V to 120V Power Cord Adapter



K5953-2 Sprinter 180Si W/ Hand Slide & Case

Includes everything in base model [K5453-1], plus:

- Caliber 17 Flexible Head TIG Torch [K4841-17F-1]
- Parts Kit for 17 Series TIG Torch [KP4760-HD]
- Linear Slide Hand Amptrol [K4361-1]
- Adjustable Gas Regulator and Hose [3100211]
- TIG Torch Adapter [K1622-7]



K5585-2 Sprinter 180Si W/ Foot Pedal & Case

Includes everything in base model [K5453-1], plus:

- Caliber 17 Series TIG Torch [K4841-17F-1]
- Parts Kit for 17 series Tig Torch [KP4760-HD]
- Foot Pedal [K4361-1]
- Adjustable Gas Regulator and Hose [3100211]
- TIG Torch Adapter [K1622-7]

PRODUCT SPECIFICATIONS

Product Name	Product Number	Input Power	Rated Output Current/Voltage/ Duty Cycle	Input Current @ Rated Output	Output Range	Open Circuit Voltage [OCV]	Dimensions H x W x D in [mm]	Net Weight lb [kg]
Sprinter 180Si	K5453-1	120/1/60	TIG: 110A/14.6V/40% STICK: 85A/23.2V/40%	120 VAC: 20A	10-140A DC TIG 20-110DC STICK	Average OCV - 65V Peak OCV - 110V VRD OCV (Peak) - 14V	11.8 x 6.25 x 16 (299.7 x 158.8 x 406.4)	19.5(8.8)
			230/1/60		10-200A DC TIG 20-180A STICK			

For best welding results with Lincoln Electric® equipment, always use Lincoln Electric consumables. Visit www.lincolnelectric.com for more details.

CUSTOMER ASSISTANCE POLICY

The business of Lincoln Electric is manufacturing and selling high quality welding equipment, automated welding systems, consumables, and cutting equipment. Our challenge is to meet the needs of our customers, who are experts in their fields, and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or technical information about their use of our products. Our employees respond to inquiries to the best of their ability based on information and specifications provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment, or to provide engineering advice in relation to a specific situation. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or communications. Moreover, the provision of such information or technical information does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or technical information, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose or any other equivalent or similar warranty is specifically disclaimed. Lincoln Electric is a responsive manufacturer, but the definition of specifications, and the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

