

# GASOLINE ENGINE-DRIVEN WELDER/GENERATORS

Select the Model That's Right for You



**OUTBACK® 185**



**RANGER® 225**



**RANGER® 260MPX™**



**RANGER® 330MPX™**



**RANGER® AIR 260MPX™**

	<b>OUTBACK® 185</b>	<b>RANGER® 225</b>	<b>RANGER® 260MPX™</b>	<b>RANGER® 330MPX™</b>	<b>RANGER® AIR 260MPX™</b>
<b>RATED OUTPUT: AMPS, VOLTS, DUTY</b>	150A, DC CC, 100A, 25V, 20%	225A DC CC, 25V, 40%	260A DC CC, 26V, 100%	330A DC CC, 28V, 100%	260A, DC CC, 26V, 100%
<b>WELD PROCESSES</b>	CC-Stick	CC-Stick, Scratch Start TIG, CV-Wire	CC-Stick, Touch Start TIG®, CV-Wire	CC-Stick, Pulse Touch Start TIG®, CV-Wire, Pipe, Gouging	CC-Stick, touch Start TIG, CV-Wire
<b>AC GENERATOR (SINGLE PHASE)</b>	5,200W Continuous 5,700W Peak	9,000W Continuous 10,500W Peak	9,500W Continuous 10,000W Peak	10,000W Continuous 11,500W Peak	9,000W Continuous 11,500W Peak
<b>CASE DIMENSIONS (H x W x D)</b>	25.6 x 21.8 x 31.5 in. (651 x 553 x 800 mm)	30 x 21.5 x 42.3 in. (762 x 546 x 1073 mm) 36.2 in. (920 mm) to top of exhaust tube	26 x 20 x 36 in. (660 x 508 x 914 mm) 28.8 in. (711 mm) to top of exhaust tube Galvanized base to increase the life of the machine and help prevent rusting	26 x 20 x 36 in. (660 x 508 x 914 mm) 28.8 in. (711 mm) to top of exhaust tube Galvanized base to increase the life of the machine and help prevent rusting	26 x 20 x 48 in. (660 x 508 x 914 mm) 29 in. (737 mm) to top of exhaust tube Galvanized base to increase the life of the machine and help prevent rusting
<b>ENGINE FUEL &amp; CAPACITY</b>	Gasoline (6.8 Gallon)	Gasoline (12 Gallon)	Gasoline (11 Gallon)	Gasoline (11 Gallon)	Gasoline (11 Gallon)
<b>ENGINE BRAND &amp; HP</b>	14 HP Kohler®	23 HP Kohler®	23.5 HP Kohler®	25 HP Kohler® (K3459-1) 25 HP Kohler® EFI (Electronic Fuel Injection) (K4779-1)	26.5 HP Kohler® ETB
<b>PRODUCT WEIGHT</b>	295 lbs. (134 kg)	514 lbs. (233 kg)	446 lbs. (202 kg)	446 lbs. (202 kg)	565 lbs. (256 kg)
<b>NOISE AT RATED LOAD SOUND LEVEL SOUND POWER (LWA)</b>	Not Available	76.4 dBA at 23 ft. (7 m)	74.7 dBA at 23 ft. (7 m)	74.7 dBA at 23 ft. (7 m)	83.5 dBA at 23 ft. (7 m)
<b>ADDITIONAL TECHNOLOGY</b>	Reactor Technology	Reactor Technology	Chopper Technology® Crosslinc® Digital UI Maintenance Screen Ready.Set.Weld® Connection for remote weld output 14-pin wire feeder connection Direct Connect Spool Gun	Chopper Technology® Crosslinc® Digital UI Maintenance Screen Ready.Set.Weld® Connection for remote weld output 14-pin wire feeder connection Direct Connect Spool Gun	Air Compressor Battery Jump/Charge Auto Start/Stop Variable Engine Speed Chopper Technology® Crosslinc® Maintenance Screen Ready.Set.Weld® Direct Connect Spool Gun

#### CUSTOMER ASSISTANCE POLICY

The business of Lincoln Electric is manufacturing and selling high quality welding equipment, automated welding systems, consumables, and cutting equipment. Our challenge is to meet the needs of our customers, who are experts in their fields, and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or technical information about their use of our products. Our employees respond to inquiries to the best of their ability based on information and specifications provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment, or to provide engineering advice in relation to a specific situation. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or communications. Moreover, the provision of such information or technical information does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or technical information, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose or any other equivalent or similar warranty is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the definition of specifications, and the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to [www.lincolnelectric.com](http://www.lincolnelectric.com) for any updated information.

**The Lincoln Electric Company**  
22801 St. Clair Avenue · Cleveland, OH · 44117-1199 · U.S.A.  
[www.lincolnelectric.com](http://www.lincolnelectric.com)