

DLF™-82 Wire Feeder

DIGITAL SEMIAUTOMATIC WIRE FEEDER



DIGITAL LINCOLN FEEDER

The DLF-82 wire feeder is the ideal feeder to pair with Flextec® power sources for Pulsed MIG*, as well as CV-MIG, welding applications. Designed to combine the latest welding innovation with easy, operator-focused control features, this wire feeder/power source solution delivers the benchmark of simplicity and performance.

Simple System Configuration – Includes integrated 5-pin ArcLink® control cable, 0.035/0.045 drive rolls, wire reel stand for up to 60-lb spools, Magnum® PRO Curve™ HDE 350.

Simple to Use – Synergic weld modes for easy one knob control. Set WFS and V is automatically adjusted.

***Pulsed MIG Support** – with pulse supporting Flextec power source – lower spatter, greater puddle control.

***Auto Settings** – run-in speed, pre-flow, post-flow, burn-back are auto-set based on setup configuration.

Memories – up to four stored weld schedules for easy changes between different welds

Limits/Lockouts – reduces chance of accidental welding out of procedure

MaxTrac Wire Drive – proven performance, consistent and reliable wire feeding

Customizable Start and Crater Settings – greater control over weld profile at start and end of weld.

*Synergic Modes, Pulsed MIG, and Auto settings are a function of the power source. These can only be accessed by the DLF-82 if they are included in the Flextec software. Flextec 350XP, Flextec 350X PowerConnect and Flextec 500X are the recommended power sources. Other Flextecs may not allow for pulsed MIG and auto settings.

Processes »

CV-MIG, CV-FCAW, Pulsed MIG

Applications »

Fabrication Shops
Welding Production Facilities

Output »



Input »



Recommended Power Sources »

Pulsed MIG Capable Power Sources

Flextec 350XP
Flextec 350X PowerConnect®
Flextec 500X

Compatible Power Sources

Flextecs with 5-pin ArcLink Connector

Product Number »

K5282-3 DLF-82 Bench Model w/wire reel stand and gun

PRODUCT NUMBERS

Product Number	Description
K5282-3	DLF-82 Wire Feeder - includes 8ft integrated ArcLink® control cable and: K5284-1 DLF Wire Reel Stand (60-lb capacity) KP1696-1 0.035/0.045 reversible V-groove drive rolls K4532-2-10-45 Magnum® PRO Curve™ HDE 350, .045, 15ft Gun Ready-Pak
K5282-2	DLF-82 Bench Model with no gun, includes 8ft integrated ArcLink control cable and: K5284-1 DLF Wire Reel Stand (60-lb capacity) KP1696-1 0.035/0.045 reversible V-groove drive rolls
K5282-1	DLF-82 Base Model wire drive only. Includes 8ft integrated ArcLink control cable
K5284-1	DLF Wire Reel Stand
K3341-1	Lift Bail
K5395-1	DLF- Feeder, Inverter Cart Mounting Kit

DRIVE ROLLS

Wire Diameter	Solid Wire (V-Groove)	Cored Wire (Knurled)	Aluminum (U-Groove)
0.023-0.030	KP1696-030S	-	-
0.035	KP1696-035S	KP1697-035C	KP1697-035A
0.035-0.045	KP1696-1	-	-
0.040	KP1696-2	-	KP1695-040A
0.045	KP1696-045S	KP1697-045C	-
3/64	-	-	KP1695-3/64A
0.052	KP1696-052S	KP1697-052C	-
1/16	KP1696-1/16S	KP1697-1/16C	KP1695-1/16A
0.068-0.072	-	KP1697-068	-
5/64	-	KP1697-5/64	-

PRODUCT SPECIFICATIONS

Product Name	Product Number	Input Power	Rated Output: Current/Voltage/ Duty Cycle	Solid Wire Diameter Range in. (mm)	Cored Wire Diameter Range In. (mm)	Wire Feed Speed Range: ipm (m/min)	Dimensions H x W x D in. (mm)	Weight lbs (kg)
DLF 82 Bench Model	K5282-3	40 VDC	500A @ 100%	0.023 - 1/16 (0.58 - 1.6)	0.030 - 5/64 (0.76 - 1.98)	50-800 (1.3 - 20.3)	15.9 x 12.0 x 25.6 (403 x 305 x 320)	43 (19.5)
			600A @ 60%					

For best welding results with Lincoln Electric® equipment, always use Lincoln Electric consumables. Visit www.lincolnelectric.com for more details.

CUSTOMER ASSISTANCE POLICY

The business of Lincoln Electric is manufacturing and selling high quality welding equipment, automated welding systems, consumables, and cutting equipment. Our challenge is to meet the needs of our customers, who are experts in their fields, and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or technical information about their use of our products. Our employees respond to inquiries to the best of their ability based on information and specifications provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment, or to provide engineering advice in relation to a specific situation. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or communications. Moreover, the provision of such information or technical information does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or technical information, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose or any other equivalent or similar warranty is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the definition of specifications, and the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.