PROJECTION-PAK

RESISTANCE & FASTENER WELDING SYSTEM



Dual Station Resistance Welder

Renders are for reference only

PROJECTION-PAK RESISTANCE & FASTENER WELDING SYSTEM

The pre-engineered Projection-Pak[™] system automates fastener and other resistance-type welding applications. The Projection-Pak system complements arc welding processes so that Lincoln Electric Automation can be your preferred one-stop shop for all your automated welding needs.

SYSTEM INCLUDES

- Upper weld gun slide configurations
- Fabricated heavy-gauge steel with gusset reinforcements
- · Copper-laminated shunts and copper buss bar connections
- · Perimeter guarding and safety light curtains

BENEFITS

- · Minimal installation time required
- Provides for "quick-change" tooling integration
- Helps increase operator safety with hand-panel guarding and single load/unload access point
- Programmable with touchscreen HMI

OPTIONS AVAILABLE


- Pneumatic and water circuit chiller
- Vibratory fastener feed & placement systems
- · Fixture tooling
- Automatic feeding and placement of fasteners


INDUSTRY

Robotic Automation Markets

CONTACT LINCOLN ELECTRIC AUTOMATION - FORT LORAMIE











sales_fortloramie@lincolnelectric.com





Publication LEA-102423KC1-02
© Lincoln Global Inc. All Rights Reserved All trademarks and registered trademarks are the property of their respective owners.
www.lincolnelectric.com/automation



| 1. Frame | - Stand-alone with fork lift access tubes | | | |
|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|
| 2. Transformers | - Roman, MFDC , water cooled, light weight - Available in 100 KVA (or) 170 KVA MFDC, water-cooled | | | |
| 3. Secondary Circuit | - Copper laminated shunts and copper buss bar connections. | | | |
| 4. Weld Gun | - Pneumatic – (single or dual gun) - Milco, fixture type - Copper, water-cooled holders with replaceable weld dies - LVDT stroke detection | | | |
| 5. Weld Control | - MFDC Inverter, water cooled - Single contactor - Dual contactor (cascade or dual-pack) – requires dual transformers | | | |
| 6. Upper Weld Gun Side Configurations | - (X-Axis) – Electrically controlled weld gun positioning – 400mm stroke (L to R) - Single Slide Configuration - 400mm stroke - Dual Slide Configuration – 220mm stroke | | | |
| 7. Lower Tooling Slide | Programmable – 300mm stroke (in/out) (Y-Axis) – Electrically controlled tooling fixture positioning Provides ease of loading/unloading of component parts. Tool-less" lower tooling changeover (quick-change concept) Tool Plate: 20in.L x 12.75in.W – Max of 60lb | | | |
| 8. Machine Control | - Power Distribution Panel (PDP) - Rockwell (A-B) PLC Panel - Armorview Plus 7 HMI – (A-B), with stack light | | | |
| Fixture Tooling (Available upon Request) | Light weight, copper coated plate with insulated part locating features Quick-change design (tool-less change-over) Pneumatic and electrical connections available Copper, water- cooled (weld stud and weld nut electrodes available) | | | |
| | 2. Transformers 3. Secondary Circuit 4. Weld Gun 5. Weld Control 6. Upper Weld Gun Side Configurations 7. Lower Tooling Slide 8. Machine Control Fixture Tooling | | | |

Description

Fabricated heavy gauge steel with gusset reinforcements

PRODUCT SPECIFICATIONS

b

| Product Number | Model | Description | MFDC Transformers KVA | MFDC Transformers Qty | MFDC Weld Control | Upper Gun Slide(s) X-Axis Left to Right (Programmable) | Lower Tool Shuttle Y-Axis Front to Back (Programmable) | Extended Guard Required |
|-------------------|------------------------|----------------------------------------|----------------------------------|-----------------------------|----------------------|-----------------------------------------------------------------|-----------------------------------------------------------------|-------------------------------|
| AD2493-1 | LEA100-1G-1T-1SL-1SCR | Single Gun / Single Slide | 100 | 1 | 1 - Single SCR | (1) 400mm | 300mm | Single |
| | LEA100-2G-1T-1SL-1SCR | Dual Gun / Single Slide | 100 | 1 | 1 - Single SCR | (1) 400mm | 300mm | Single |
| | LEA100-2G-1T-2SL-1SCR | Dual Gun / Dual Slide / Single SCR | 100 | 1 | 1 - Single SCR | (2) 220mm | 300mm | Both |
| | LEA100-2G-2T-2CAS | Dual Gun / Dual Slide / Dual SCR CAS | 100 | 2 | 1 - Dual SCR | (2) 220mm | 300mm | Both |
| | LEA100-2G-2T-2SL-2PACK | Dual Gun / Dual Slide / Dual SCR 2PACK | 100 | 2 | 1 - Dual SCR | (2) 220mm | 300mm | Both |
| | LEA170-1G-1T-1SL-1SCR | Single Gun / Single Slide | 170 | 1 | 1 - Single SCR | (1) 400mm | 300mm | Single |
| | LEA170-2G-1T-1SL-1SCR | Dual Gun / Single Slide | 170 | 1 | 1 - Single SCR | (1) 400mm | 300mm | Single |
| | LEA170-2G-1T-2SL-1SCR | Dual Gun / Dual Slide / Single SCR | 170 | 1 | 1 - Single SCR | (2) 220mm | 300mm | Both |
| | LEA170-2G-2T-2CAS | Dual Gun / Dual Slide / Dual SCR CAS | 170 | 2 | 1 - Dual SCR | (2) 220mm | 300mm | Both |
| | LEA170-2G-2T-2SL-2PACK | Dual Gun / Dual Slide / Dual SCR 2PACK | 170 | 2 | 1 - Dual SCR | (2) 220mm | 300mm | Both |
| Custom | | | Based on Customer Specifications | | | | | |

Key Features

1. Frame

Important Note: Changes from recommended motor sizing, payload, duty cycles, cable routing, weld grounding (if applicable), other system specifications (i.e. controller stop parameter), and/or modifications may affect cycle times and overall performance. User assumes all responsibility for proper rigging, installation, and machine setting alignments of product(s). Manufacturer's warranty is void to the extent any failure caused by improper installation, modification, or operation by customer.

CUSTOMER ASSISTANCE POLICY

The business of Lincoln Electric is manufacturing and selling high quality welding equipment, automated welding systems, consumables, and cutting equipment. Our challenge is to meet the needs of our customers, who are experts in their fields, and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or technical information about their use of our products. Our employees respond to inquiries to the best of their ability based on information and specifications provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment, or to provide engineering advice in relation to a specific situation or application. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or technical information des not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or technical information or technical information provided to respective that might arise from the information or technical information or express or any other equivalent or similar warranty of merchantability or any warranty of fitness for any customers' particular purpose or any other equivalent or similar warranty is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the definition of specifications, and the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

THE LINCOLN ELECTRIC COMPANY 22801 Saint Clair Avenue · Cleveland, OH · 44117 · U.S.A. Phone: +1216.481.8100 · www.lincolnelectric.com