

MODEL 1031 ANNUNCIATOR

TWO-CHANNEL REMOTE ALARM PANEL



The Harris Model 1031 two-channel remote alarm panel offers two input and two output channels, along with dry contact relay outputs and normally open output capabilities. Other features include a highly visible lighted status notification, a distinctive audible notification, auto-reset when cylinders are replenished, an audible alarm silence feature, the ability to "Daisy Chain" multiple alarm panels together, and Class I, Division II status with a NEMA 4 rating.

FEATURES

- Two input channels
- Two output channels
- Dry contact relay outputs
- Normally open output capability
- Highly visible lighted status notification
- Distinctive audible notification
- Auto-reset when cylinders are replenished
- Audible alarm silence feature
- Ability to "Daisy Chain" multiple alarms
- Class I Division II

SPECIFICATIONS

Audio

95 DB audible alarm

Power

120VAC or 220VAC
6V AC/DC to 24 V AC/DC

Environment

NEMA 4

Outputs

2 channels
Dry contacts,
Normally open/500 mh each
Contact Rating .5A 24V

Inputs

2 channels
Accepts normally open
Over current Protected Auto Reset

Connectors (Bulgin)

Input: 6 pin circular
Output: 6 pin circular

Dimensions

4.5" x 3.25" x 2.25"

RELATED OPTIONS

- P/N: 9030381 50-ft. Extension Cable
P/N: 9030382 100-ft. Extension Cable
P/N: 9030383 Conductor cable replacement

MODEL 1031 ORDERING INFORMATION

PART NO.	DESCRIPTION	EXTENSION CABLE
9030318	Two-Channel Alarm Panel, chrome	25'
4300823	Two-Channel Alarm Panel w/single gauge 3,000 psig for reg.	25'
4300824	Two-Channel Alarm Panel w/ single gauge SS. 3,000 psig for reg.	25'
4300825	Two-Channel Alarm Panel w/2 gauges for 900 and 905 series, chrome	25'
4300826	Two-Channel Alarm Panel w/2 gauges for 900 and 905 series, stainless steel	25'
4300827	Two-Channel Alarm Panel w/2 gauges for gas phase Dewar service, chrome	25'
4300828	Two-Channel Alarm Panel w/2 gauges for gas phase Dewar service, stainless steel	25'