GAS CYLINDER JACKET



MATERIALS

Closed cell foam insulation
Silicone impregnated fiberglass line
Polyester exterior

When mixing several hydrocarbon components in a cylinder and exposing the cylinder to low temperatures the hydrocarbon will become a sticky mess. The heavier molecules will stick to the cylinder walls causing problems with the accuracy of the mixture. To prevent this from happening, Harris' cylinder jacket features a self-limiting heated cable that prevents overheating. This cable heats up to 120°F. It is designed to maintain the temperature of the hydrocarbon above its dew point, keeping the gas from stratifying. Harris' cylinder jacket is constructed of materials approved by UL® for Class 1 Division 2, Group B, C, and D hazardous locations.

FEATURES

- Prevents hydrocarbons mixtures from stratifying and insulates to prevent the content from condensing
- Silicone-impregnated fiberglass liner and polyester exterior provides protection from the elements
- Fluoropolymer over jacket protects the heat cable from corrosion
- D-rings with Velcro® line provides a snug closure to keep the heat in
- Applications natural gas, power plants and utilities

SPECIFICATIONS

Maintain Temperature: @70°F Ambient: 120°F - @0°F Ambient: 60°F
 Electrical Classifications: Class 1 Division 2 Groups B. C. and D

Power Requirements: 120 Voltage (240 Voltage option)

Power Output: 8 watts/ft at 50°F

Flexible Conduit: 10' of 3 color coded conductors

ORDERING INFORMATION

| | ORDERING NO. | CYLINDER SIZE | DIMENSIONS | ELECTRICAL |
|---|--------------|---------------|------------|----------------------|
| _ | 9030154 | 150A, AL,1R | 11" x 48" | 12' of internal wire |
| _ | 9030148 | 350, XL, 1F | 17" x 45" | 19' of internal wire |
| _ | 9030157 | LP5 | 14" x 18" | 5' of internal wire |
| _ | | | | |

NOTE: These jackets are not designed to heat up cylinders that have been in cold or freezing environments. Cold cylinders need to be brought up to temperature before using the blanket. Excess heat lost can be experience through the top of the cylinder jacket. Harris recommends the regulator hood blanket to prevent this heat lost.

RELATED OPTIONS

| 9030160 | HOOD BLANKET | |
|---------|--------------|--|

NOTE: Other sizes available - call customer service @1.800.733.4043 option 2

harrisspecgas@lincolnelectric.com



The Harris Products Group A Lincoln Electric Company 4501 Quality Place - Mason, OH 45040 Customer Service: 1.800.733.4043 PROMPT 2 Fax: 513.754.8778



