INERTFIL 308L

TOP FEATURES

- The low carbon content reduces the propensity to intergranular carbide precipitation, which increases the resistance to intergranular corrosion without the use of stabilizers.
- The weld metal provides good corrosion resistance properties to intergranular attack from a range of liquid media at service temperatures up to 300°C.
- Excellent mechanical strength and corrosion resistance.

CLASSIFICATION

AWS A5.9 ER308L EN ISO 14343-A G 19 9 L

SHIELDING GASES (ACC. EN ISO 14175)

M12 Mixed gas Ar+ 0.5-5% CO₂ M13 Mixed gas Ar+ 0.5-3% O₂

TYPICAL APPLICATIONS

- Pipework
- Petrochemical
- Nuclear Power generation
- Cladding

APPROVALS

τüν	DB	CE
+	+	+

CHEMICAL COMPOSITION (WEIGHT %), TYPICAL, WIRE

С	Mn	Si	Р	S	Cr	Ni
0.020	1.8	0.45	≤0.025	≤0.020	20	10

MECHANICAL PROPERTIES, TYPICAL, ALL WELD METAL

	Shielding gas	Condition*	Yield strength	Tensile strength	Elongation	Impact ISO-V (J)	
	Silleluling gas	Condition	(MPa)	(MPa)	(%)	+20°C	-196°C
Typical values	M13	AW	≥350	≥520	≥35	≥140	≥40

^{*} AW = As welded

PACKAGING AND AVAILABLE SIZES

Wire diameter (mm)	Packaging	Weight (kg)	ltem number	
1.0	SPOOL (BS300)	15.0	W000282986	
1.2	SPOOL (BS300)	15.0	W000282988	

TEST RESULTS

Test results for mechanical properties, deposit or electrode composition and diffusible hydrogen levels were obtained from a weld produced and tested according to prescribed standards, and should not be assumed to be the expected results in a particular application or weldment. Actual results will vary depending on many factors, including, but not limited to, weld procedure, plate chemistry and temperature, weldment design and fabrication methods. Users are cautioned to confirm by qualification testing, or other appropriate means, the suitability of any welding consumable and procedure before use in the intended application

Safety Data Sheets (SDS) are available here:



Subject to Change – The information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.eu for any updated information.

