

SG 920

Automatic Switchover System



The SG 920 BR / SG 920 SS semi-automatic high purity switchover prevents downtime by automatically switching gas supply from the primary cylinder bank to the reserve cylinder bank. The user resets the primary bank by turning the knob. Manual adjustment of the individual regulators is not required.

All systems include a line control regulator.

FEATURES

- Maximum inlet pressure 3000 PSIG
- Delivery pressure: 0-100, 0-200 PSIG
- Inlet/outlet - 1/4" NPT
- Headers include diaphragm-type shut-off valves
- All systems include stainless steel pigtails with check valves and stainless steel inner core
- Includes inlet and outlet isolation valves
- All pigtails have protective armor casing for added safety

RELATED OPTIONS

- 4302673 - G 277 Two Cylinder Process Station
- 4302675 - G 400P Four Cylinder Process Station
- 4302676 - G 600P Six Cylinder Process Station
- 4300329 - Remote alarm box

SPECIFICATIONS

MODEL	MAXIMUM INLET PRESSURE	MAXIMUM FLOW RATE	DELIVERY RANGE
920	3000 PSIG	200 SCFH	100 PSIG
920 HP	3000 PSIG	250 SCFH	200 PSIG

SG 920 ORDERING INFORMATION

SG 920 BR / SG 920 SS	XX(XX)	XX(XX)	XXX
	Right Header (# CYLINDERS)	Left Header (# CYLINDERS)	Gas Service
<div>920 BR (100PSI)</div> <div>920 BR HP (200PSI)</div> <div>920 SS (100PSI)</div> <div>920 SS HP (200PSI)</div>	24” Pigtails	24” Pigtails	320 - Carbon Dioxide 346 - Air (Breathing) 350 - Hydrogen 500 - Medical Mixtures 540 - Oxygen 580 - N2/He/Ar 590 - Air (Industrial) 660 - Corrosive Gases (920 SS only) 330 - Corrosive Gases (920 SS only)
	1R	1L	
	2R	2L	
	3R	3L	
	4R	4L	
CUSTOM CONFIGURATIONS AVAILABLE UPON REQUEST. CONTACT CUSTOMER SERVICE.	36” Pigtails	36” Pigtails	
	1R36	1L36	
	2R36	2L36	
	3R36	3L36	
	4R36	4L36	

Orders: 1.800.733.4043

THE HARRIS PRODUCTS GROUP
www.harrisproductsgroup.com

