

NEW!

THE LINCOLN ELECTRIC COMPANY

Introducing the Speed-Feed® SlimReel™



Lincolnweld®



New 250 lb. (113.4 kg) Package for Submerged Arc Wire

- ▶ **Ideal for Wind Tower Manufacturing** – Fits directly into most manipulator set-ups.
- ▶ **6.25 in. (158.8 mm) Reel Width** – Thin reel for easy conversion.
- ▶ **Available for Lincolnweld® L-61 Wire** – Additional alloys available upon request.
- ▶ **For Optimal Wind Tower Welding Performance** – Pair Lincolnweld® L-61 SlimReel™ with Lincolnweld® WTX flux.

PRODUCTS AND DIAMETERS AVAILABLE

Product Name	Diameter in. (mm)	Product Number
Lincolnweld® L-61	3/32 (2.5)	ED033074
	1/8 (3.2)	ED033075
	5/32 (4.0)	ED033076
	5/32 (4.0)	ED033123*

*Note: Each lot tested with Lincolnweld® WTX flux. Certificates available online.

Lincoln SlimReel™ vs. ESAB 200 lb. (90.7 kg) Coil

- ▶ **SlimReel™ Requires No Adapter** – Lightweight and easier to load and unload!
- ▶ **50 More Pounds of Wire** – Same overall weight!