Fewer Cables. More Control.

NEW CrossLinc® Remote

Remote control without control cables! Use with CrossLinc®-equipped Flextec® welders to adjust the weld setting remotely at the arc, including current for stick and TIG welding processes and voltage when used with a wire feeder.

That means a safer construction site, higher quality welds, more productivity and reduced costs.

FEATURES

- Remotely control welding current for Stick, TIG and Gouging processes
- Compatible with older non-CrossLinc equipped wire feeders[1] to remotely control welding voltage.
- Tough construction – Sturdy steel case and rugged rubber corner bumpers
- Compatible with Stick, TIG or Wire welding processes, CC/CV, DC+/-
- Allows presetting of welding output.
- Shows actual arc voltage and current during welding
- Polarity sensing capability allows for automatic process change between Stick and TIG processes
- Digital meters indicate polarity prior to welding
- Memory function remembers settings when disconnected
- Foldable handle allows easy transport and a place to hang the remote at the work site
- Automatic pairing with the CrossLinc equipped welder when powered up

[1] Compatible as remote voltage control with LN-25, LN-25 PRO without digital meters, Activ8®

Publication MC16-137 | Issue Date 01/17

www.lincolnelectric.com

LINCOLN® ELECTRIC

SPECIFICATIONS

Product Number	Description	Rated Output (amps@Duty Cycle)	Dimensions H X W x D in. (mm)	Net Weight lbs (kg)
K4345-1	CrossLinc Remote	425@100% 550@60%	7.75 x 10.0 x 4.5 (197 x 254 x 114)	10.0 (4.5)

Recommended Processes

SMAW
GTAW
Arc Gouging
GMAW
FCAW-G
FCAW-S

Recommended Welding Power Sources

Flextec 350X models (excluding early model code numbers: 12464, 12610, 12321, 12611, 12465, 12612)
Flextec 650X models

Recommended Industries

Structural
Shipbuilding
Power Generation
Offshore

Flextec 350X models

Flextec 650X models

Recommended Accessories

Product Number	Description
K2485-2	2/0 Weld Cable With LC40 Male And Female Connector - 50 ft. (15.2 m)
K2485-3	3/0 Weld Cable With LC40HD Male And Female Connector - 50 ft. (15.2 m)
K3416-70	LC40 Female Connector (1/0 Thru 2/0)
K3416-90	LC40HD Female Connector (3/0 Thru 4/0)
K3417-70	LC40 Male Connector (1/0 Thru 2/0)
K3417-90	LC40HD Male Connector (3/0 Thru 4/0)



* For additional Lincoln cables and connectors, visit www.lincolnelectric.com

The Lincoln Electric Company
22801 St. Clair Avenue · Cleveland, OH · 44117-1199 · U.S.A.

www.lincolnelectric.com