TECHNICAL INFORMATION SHEET

W1060 OXY-FUEL GAS TORCH ROD

NOMINAL COMPOSITION:

Carbon	0.08% max
Manganese	0.50% max
Sulfur	0.04% max.
Nickel	0.30% max.
Aluminum	0.02% max.
Iron	Balance

Chromium	0.20% max.
Copper	0.30% max.
Silicon	0.10 %
Phosphorus	0.035% max.
Molybdenum	0.20% max.

W1060 a copper coated gas welding rod for welding carbon steel that has a maximum tensile strength of 45,000. W1060 is an excellent welding rod for thin sections up to ¼ steel plates, piping, automotive industry, and ornamental art work, No flux is needed, use a neutral flame.

Applications

- Low carbon steel
- Automotive repair
- Ornamental art

SPECIFICATION COMPLIANCE:

AISI/AWS A5.2 & ASME SFA 5.2 classification R45

WARNING: PROTECT yourself and others. Read and understand this information. FUMES AND GASES can be hazardous to your health.

HEAT RAYS, (infrared radiation) from flame or hot metal can injure eyes.

- Before use, read and understand the manufacturer's instructions, Safety Data Sheets (SDS), and your employer's safety practices.
- Keep your head out of fumes.
- Use enough ventilation, exhaust at the flame, or heat source, to keep fumes and gases from your breathing zone and the general area.
- Wear correct eye, ear, and body protection.
- See American National Standard Z49.1, Safety in Welding, Cutting, and Allied Processes, published by the American Welding Society, 8669 Doral Blvd., Doral, Florida 33166; OSHA Safety and Health Standards, available from the U.S. Government Office, Washington, DC 20402.

STATEMENT OF LIABILITY- DISCLAIMER:

Any suggestion of product applications or results is given without representation or warranty, either expressed or implied. Without exception or limitation, there are no warranties of merchantability or of fitness for particular purpose or application. The user must fully evaluate every process and application in all aspects, including suitability, compliance with applicable law and non-infringement of the rights of others. The Harris Products Group and its affiliates shall have no liability in respect thereof.