VdTÜV-Kennblatt for welding consumables

	1 Manufacturer/Supplier ASKAYNAK TUR Istanbul	2 No. of VdTÜV-Kennblatt: 12335.02 11.2013

3 Welding consumable*:	Stabelektrode
4 Trade name*:	AS P - 316L Super
7 Type*:	EN ISO 3581-A - E 19 12 3 LR 1 2
11 Diameter range:	3,2 bis 4,0 mm
12 Auxiliary materials:	---

13 The validity of this Kennblatt will be certified,respectively, in the latest edition of CD-ROM TÜV-eignungsgeprüfte Schweißzusätze

15 Materials and postweld heat treatment

Pos	Wb	Group / Material 1	Text	Group / Material 2	Remarks
	U	Gruppe 8.1			

16 Material groups acc. to CR ISO 15608

21 Root weldability:	not verified
23 Wall thickness:	max. 30 mm
24 Type of current and polarity:	G+, W
25 Welding position according to DIN EN ISO 6947:1997-05:	PA, PB, PC
26 Highest operating temperature in the short-term range as for parent metal, but not higher than:	350°C
27 Highest operating temperature in the long-term range max.:	---°C
28 Lowest operating temperature/as for parent metal, but not lower than:	-60°C
29 Design stress value/as for parent metal:	wie Grundwerkstoff
30 For use in the long-term range:	---
31 Resistance to intergranular corrosion proven in accordance with:	---

32 Remarks:
---

33 The approval test was done on the basis of VdTÜV-Merkblatt 1153.Where nothing different is said under the heading -Remarks-, this welding consumable is suitable provided Annex I Point 4 of the Pressure Equipment Directive 97/23/EC is observed.

34 Explanations				
	A tempered	S stress-relieved	W soft annealed	G+ direct current plus pole
	L solution annealed and quenched	St stabilized		G- direct current minus pole
	N normalized	U non-annealed		W alternating current
		V hardened and tempered		

35 Compiled in accordance with the data of: TÜV NORD

*) Statements of the manufacturer