

HARRIS®

PREMIUM WELDING HOSES



4300530



KH578



6030102



4300847



HARRIS® hoses meet RMA/CGA IP-7 standard for hoses that are to be used for cutting, welding, brazing or heating applications. All Harris hoses have an internal tube and a separate external protective sheath to protect against abrasion and flames.

Grade R - For acetylene only.

Internal tubing and external sheath are not flame and oil resistant.

Grade T – For all fuel gases. Internal tubing and external sheath are flame and oil resistant. The Grade T hose provides added protection by being self extinguishing when exposed to a flame, slag or other hot materials.



Internal Tube

External Protective Sheath



Hydraulic Crimped Connections



Repeating hose identification imprinted along the length for positive identification.



While separate, the hoses are fused together to prevent entanglement.

PART NO.	DESCRIPTION	GRADE
6030102	HOSE, 1/4 X 25 BB	GRADE T
4300530	HOSE, 1/4 X 50 BB	GRADE R
4300847	HOSE, 3/8 X 50 BB	GRADE T
KH578	HOSE, 1/4 X 25 BB	GRADE R
6030103	HOSE, 1/4 X 50 BB	GRADE T
6030104	HOSE, 1/4 X 100 BB	GRADE T
4300848	HOSE, 3/8 X 100 BB	GRADE T

The Harris Products Group
 A Lincoln Electric Company
 4501 Quality Place - Mason, OH 45040
 Customer Service: 1.800.733.4043
 Fax: 513.754.8778
 www.harrisproductsgroup.com

092020



A LINCOLN ELECTRIC COMPANY

Turn to the Pros