

LN-25 PRO[®] Dual Power

SEMI-AUTOMATIC WIRE FEEDER



Shown:
LN-25 PRO Dual Power
(K2614-6)

PORTABLE INDUSTRIAL WIRE FEEDER

LN-25 PRO Dual Power Wire Feeder can be used as an across the arc powered feeder or with a 14-pin control cable. It is designed to be simple, reliable and easy to service. These voltage-sensing feeders are compatible with any CV welding power source. Whether you are an ironworker, pipeline welder, or weld at a construction site, shipbuilding facility or metal fabrication shop, we have the right semi-automatic wire feeder for you.

Processes »

MIG, Flux-Cored

Applications »

Construction, Shipbuilding, Rental Fleet, Pipe, Metal Fabrication

Output »



Input »



All Models
Across the Arc



K2614-6 Only
Control Cable

Product Number »

K2614-6 PRO Dual Power

FEATURES

- **MAXTRAC® Wire Drive System** – Heavy-duty cast aluminum wire drive system provides reliable feeding and more durability.
- Tachometer feedback allows for accurate wire feed speed.
- **Dual Range Wire Feed Speed** – Delivers greater precision at low end wire feed speeds.
- **Trigger Interlock Switch** – Provides enhanced operator comfort for long welds.
- **Replaceable and Flame Resistant Case** – Can be replaced in less than five minutes.
- **Potted PC Boards** – For moisture and corrosion protection.

CONTROLS

1. Wire Feed Speed/Amperage Digital Display
2. Wire Feed Speed LED
3. Amperage LED
4. Wire Feed Speed Knob
5. 5-Pin Gun Trigger Connector
6. Work Sense Clip Connection
7. Thermal LED
8. Voltage Digital Display
9. Voltage LED
10. Remote Voltage Control Knob (not presettable)
11. Gas Purge Pushbutton
12. Flow Meter Valve
13. Shielding Gas Inlet
14. 14-Pin Control Cable Input
15. Electrode Lead

NOTE: In across-the-arc mode, voltage knob does not control voltage. Must be adjusted at power source.



ACCESSORIES

FEED PLATE GUN ADAPTERS

K1500-1 ⁽¹⁾	K1500-2 ⁽²⁾	K1500-3	K1500-4	K1500-5	K489-7
Lincoln Electric	Tweco® #2 - #4	Tweco #5	Miller® Guns	OXO® Guns	Fast-Mate™ / Euro Connector
Compatible gun connector kits:	Compatible gun connector kits:	Compatible gun connector kits:	Compatible gun connector kits:		Compatible with weld guns with Fast-Mate or Euro connectors
K466-1 K613-1 K613-6 K466-8	K466-10 K466-2 K466-6	K613-7 K613-2	K466-3 K613-3		
					

⁽¹⁾Included with machine. ⁽²⁾Installed in machine.

Tweco® is a registered trademark of Victor Technologies. Miller® is a registered trademark of Miller Electric Mfg. Co. OXO® is a registered trademark of Miller Electric Mfg. Co.

MAXTRAC DRIVE ROLL & WIRE GUIDE KITS

Description	Product Number
Steel Wire Sizes (includes stainless steel):	
.023-.030 in (0.6-0.8 mm)	KP1696-030S
.035 in (0.9 mm)	KP1696-035S
.045 in (1.2 mm)	KP1696-045S
.052 in (1.4 mm)	KP1696-052S
.035, .045 in (0.9, 1.2 mm)	KP1696-1
.040 in (1.0 mm)	KP1696-2
1/16 in (1.6 mm)	KP1696-1/16S
Cored Wire Sizes:	
.030-.035 in (0.8-0.9 mm)	KP1697-035C
.040-.045 in (1.0-1.2 mm)	KP1697-045C
.052 in (1.4 mm)	KP1697-052C
1/16 in (1.6 mm)	KP1697-1/16C
Steel or Cored Wire Sizes:	
.068-.072 in (1.8 mm)	KP1697-068
5/64 in (2.0 mm)	KP1697-5/64
3/32 in (2.4 mm)	KP1697-3/32
Aluminum Wire Sizes:	
.035 in (0.9 mm)	KP1695-035A
.040 in (1.0 mm)	KP1695-040A
3/64 in (1.2 mm)	KP1695-3/64A
1/16 in (1.6 mm)	KP1695-1/16A

WELD POWER CABLES

Description	Product Number	
1/0 Cable	Twist Mate™ to Lug, 1/0, 350A, 60% duty cycle, 10 ft. (3.0 m)	K1840-10
	Twist Mate to Twist Mate, 1/0, 350A, 60% duty cycle, 25 ft. (7.6 m)	K1841-25
2/0 Cable	Tweco-Style male plug and female receptacle, 2/0, 350A 60% duty cycle, 50 ft. (15.2 m)	K2485-2
	Tweco-Style male plug and 0.53 in. lug, 2/0, 350A, 60% duty cycle, 50 ft. (15.2 m)	K2484-2
	Twist Mate to Twist Mate, 2/0, 350A, 60% duty cycle, 50 ft. (15.2 m)	K1841-50
3/0 Cable	Tweco-Style male plug and female receptacle 3/0, 600A, 60% duty cycle, 50 ft. (15.2 m)	K2485-3
	Tweco-Style male plug and 0.53 lug, 3/0, 600A, 60% duty cycle, 50 ft. (15.2 m)	K2484-3
	Lug to Lug, 3/0, 600A, 60% duty cycle, 10 ft. (3.0 m)	K1842-10
	Lug to Lug, 3/0, 600A, 60% duty cycle, 35 ft. (10.6 m)	K1842-35
4/0 Cable	Lug to Lug, 3/0, 600A, 60% duty cycle, 60 ft. (18.2 m)	K1842-60
	Lug to Lug, 4/0, 600A, 60% duty cycle, 110 ft. (33.5 m)	K1842-110

CONTROL EXTENSION CABLES (FOR DUAL POWER MODEL ONLY)

Description	Product Number
Control Cable Extension, 10 ft. (3.0 m) - Male 14-pin to Female 14-pin	K1797-10
Control Cable Extension, 25 ft. (7.6 m) - Male 14-pin to Female 14-pin	K1797-25
Control Cable Extension, 50 ft. (15.2 m) - Male 14-pin to Female 14-pin	K1797-50
Control Cable Extension, 100 ft. (30.4 m) - Male 14-pin to Female 14-pin	K1797-100

RECOMMENDED ACCESSORIES



K126 PRO Innershield® Gun
350 A, 60% duty cycle air-cooled gun for flux-cored self-shielded Innershield welding. Magnum PRO expendable parts.
Order K126-11 (15 ft/4.5 m, K613-6 Gun Connector)
Order K126-12 (15 ft/4.5 m, K466-10 Gun Connector)
See publication E12.111



Magnum Self-Shielded Gun and Cable Assemblies
Available 250-600 amps.
See publication E12.110



Magnum PRO Gun and Cable Assemblies
250-550 amps, air-cooled, gas-shielded welding guns.
See publication E12.01



Magnum PRO Curve Semiautomatic Guns
Magnum PRO Curve guns for MIG or flux-cored, gas-shielded welding. Combine our classic curved handle with our Copper Plus™ contact tips and Magnum PRO gun expendables to deliver long hours of fabrication welding with less frequent tip and gun expendable parts changes.
See publication E12.05



Magnum PRO Curve HDE™ 250 Guns
Magnum® PRO Semi-Automatic MIG welding gun with 250A 100% mixed gas duty cycle. Designed to maximize performance and operator comfort.
see Publication E12.08.1, E12.08



Prewflow, Postflow and Burnback Time Kit
Provides adjustable delay of power source output shut off to prevent electrode sticking in crater when using high wire feed speeds.
Order K2330-2



Work and Wire Feeder 2/0 Weld Cable Package
Includes Twist Mate connectors, work clamp, 15 ft. (4.5 m) work cable and 10 ft. (3.0 m) electrode cable. Rated 350 amps, 60% duty cycle.
Order K1803-1



Weld Cable Package Work & Power Lead 2/0 - Tweco Male & GC500 / Tweco Male & Lug - 10 ft (3 m)
Includes Tweco-style Cam-Lock connectors, work clamps, 10 ft. (3.0 m) work cable and 10 ft. (3.0 m) electrode cable. Rated 350 amps, 60% duty cycle.
Order K1803-2



Weld Cable Package - Work Lead - TM & GC500 Ground Clamp (2/0, 350A, 60%) - 15 ft (4.5 m)
Includes Twist Mate (Dinse) connector, ground clamp, 15 ft. (4.5 m) 2/0 cable. Rated 350 amps, 60% duty cycle.
Order K1803-3



Work Clamp
Jaws open full 2-1/2 in. (63 mm). Welding cable lug bolts directly to the work clamp. 60% duty cycle. Select K910-1 for 300 Amp applications. K910-2 for 500 Amp.
Order K910-1 & K910-2



Tweco-Style Plug
Female, 1/0 through 2/0.
Order K3416-70



Tweco-Style Receptacle
Female, 1/0 through 2/0.
Order K3417-70



Tweco-Style Plug
Male, 3/0 through 4/0.
Order K3416-90



Tweco®-Style Receptacle
Female, 3/0 through 4/0.
Order K3417-90



Deluxe Adjustable Gas Regulator
Deluxe Gas Regulator for Mixed Gases, Adapter for CO₂ and 10 ft. (3.0m) Hose.
Order K586-1



Wire Feed Speed Meter
A wire feed speed meter with digital display.
Order K283



Jumper Plug Kit
For use with CV only power sources with 14 pin MS-type wire feeder connections and no contactor control switch. Jumper plug kit closes contactor for always hot welding output.
Order K484



14 Lb. Innershield Coil Adapter
Permits 14 lb. (6 kg) Innershield® electrode coils to be mounted on 2 in. (51 mm) O.D. spindles. Wire not included.
Order K435



8 In. O.D. Spool Adapter
For small spools. Permits 8 in. (203 mm) O.D. spools to be mounted on 2 in. (51 mm) or 2.5 in. (64 mm) O.D. spindles.
Order K468



Replacement Case Kit
Replace a damaged case without replacing the entire unit.
Order K2596-2 (plastic)



Twist Mate Cable Plug
For connecting welding cable to output terminal receptacles. For 2/0 - 3/0 (70 - 90 mm²) cable.
Order K852-95

PRODUCT SPECIFICATION

Product Name	Product Number	Input Power	Output Capacity Current/Duty Cycle	Flow Meter	Wire Feed Speed Range ipm (m/min)	Wire Size Range - in. (mm)			Dimensions H x W x D in (mm)	Net Weight lb (kg)
						Solid	Cored	Aluminum		
LN-25 PRO Dual Power	K2614-6	15-110 VDC or 24-42 VAC	450A/60%	Yes	50-700 (1.3-17.7)	0.023-1/16 (0.6-1.6)	0.030-5/64 (0.8-2.0)	0.035-1/16 (0.9-1.6)	15 x 8.7 x 23.2 (381 x 221 x 589)	Approx. 38 (17) (varies per model)

For best welding results with Lincoln Electric® equipment, always use Lincoln Electric consumables. Visit www.lincolnelectric.com for more details.

CUSTOMER ASSISTANCE POLICY

The business of Lincoln Electric is manufacturing and selling high quality welding equipment, automated welding systems, consumables, cutting equipment and EV charging systems. Our challenge is to meet the needs of our customers, who are experts in their fields, and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or technical information about their use of our products. Our employees respond to inquiries to the best of their ability based on information and specifications provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment, or to provide engineering advice in relation to a specific situation or application. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or communications. Moreover, the provision of such information or technical information does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or technical information, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose or any other equivalent or similar warranty is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the definition of specifications, and the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.