

ARC TRACKER™ AIR

ON-PREMISE ARC TIME MONITORING



FROM NO VISIBILITY TO KNOWING INSTANTLY

See arc-on time as it happens across machines, operators, jobs, and shifts. Arc Tracker™ Air uses universal, brand-agnostic trackers and a private long-range network to deliver real-time weld activity without relying on plant Wi-Fi or the corporate LAN.

Plug-and-play onboarding and self-configuring coverage make it easy to start with a pilot and scale across changing layouts, multi-bay facilities, and outdoor jobsites. Simple dashboards help teams identify patterns, coach constructively, and plan with greater confidence.

Real-Time Tracking – Monitor active and idle machines during the shift

Flexible Tagging – Connect activity to an operator, machine, station, or job

Historical Insight – Retain one year of data and export for analysis or integration

PRODUCT OPTIONS »

K6093-1 Arc Tracker Air Package
K6093-2 Arc Tracker Air Tracker
K6093-3 Arc Tracker Air Hub

Key Specifications »

- Connects to virtually any welding power source
- Private long-range mesh network wireless range 500 to 1,000 ft
- Up to 50 active trackers per hub
- Up to 3-year life using standard AA batteries
- IP68 enclosed, tamper-resistant tracker
- Encrypted RF communications
- No firewall changes, VPNs, or server builds
- One-year data retention

PRODUCT SPECIFICATIONS

Product	Part Number	Specification	Description	Dimensions in (mm)	Weight lb (kg)
Arc Tracker™ Air Package (10-Tracker Starter Pack)	K6093-1		Includes 10 Trackers and 1 Hub	19.30 x 11.78 x 4.37 (490 x 299 x 111)	15.75 (7.14)
Arc Tracker™ Air Tracker (Single) (Up to 50 Per Hub Installation)	K6093-2	Input Power Temperature Rating Environmental Rating Battery Life Transmission Range Sensing Range Mounting Certifications	2x AA Batteries -40°F to 185°F [-40°C to 85°C] IP68 2-3 years Exterior range expectation up to 1000 feet Interior range expectation up to 500 feet 150 - 1500 Amps Dual Cable Clamps for 1/0 to 4/0 cables FCC 15.247 FCC CLASS B EN610101:2010/A1:2019,CB IC RSS-247	6.06 x 2.68 x 3.13 (154 x 68 x 80)	0.60 (0.27)
Arc Tracker™ Air Hub (Single)	K6093-3	Input Power Temperature Rating Environmental Rating Display Size Display Resolution Port for external display Certifications	100-240 VAC Single Phase 32°F to 104°F [0°C to 40°C] None 22 inch HD LCD 1920 x 1080 HDMI FCC 15.247 FCC CLASS B EN62368-1:2024, CB IC RSS-247	19.30 x 11.78 x 4.37 (490 x 299 x 111)	10.75 (4.88)

CUSTOMER ASSISTANCE POLICY

The business of Lincoln Electric is manufacturing and selling high quality welding equipment, automated welding systems, consumables, cutting equipment and EV charging systems. Our challenge is to meet the needs of our customers, who are experts in their fields, and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or technical information about their use of our products. Our employees respond to inquiries to the best of their ability based on information and specifications provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment, or to provide engineering advice in relation to a specific situation or application. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or communications. Moreover, the provision of such information or technical information does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or technical information, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose or any other equivalent or similar warranty is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the definition of specifications, and the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.