FLEET[™]500

SIMPLE AND RUGGED



Powerful

- Weld at 500A at 30V, 40% duty cycle, even at 40°C
- 5025 Watts of Auxiliary Power available between a 240V Euro receptacle and a 120V Euro receptacle

Dependable

- Proven Chopper Technology[™] delivers easy arc starting, smooth arc action, and low spatter levels
- Desert Duty Rated™

Simple

- Easily choose between Stick, Pipe, Gouge, or TIG modes with single selector switch
- · Pipe mode offers sloped volt/amp curve for pipe welding
- Arc Force control allows the operator to adjust for a soft buttery arc or a more forceful digging arc

Processes »

Stick, TIG, Gouging, Pipe

Output »





Input »



Applications »

- Maintenance and Repair,
- Construction
- Pipeline







MACHINE SPECIFICATIONS

Product Name	Product Number	Description	Rated DC	DC Current	Auxiliary Power	Dimensions HxWxD in (mm)	Net Weight Ib (kg)
FLEET 500	K4338-2	500A DC Engineered DC Generator	At 40°C 500A/30V/40%	Stick Mode 30-500A Pipe Mode 30-300A TIG Mode 20-250A Gouge Mode 90-450A	60Hz / 240V / 15A 60Hz / 120V / 15A (5025 Watts Total)	35.9 x 25.3 x 60.0 [913 x 642 x 1524] To top of exhaust tube 46.2 (1174)	1230 (559)

ENGINE SPECIFICATIONS

			Horsepower &		Operation		
Product Name	Engine Model	Description	Displacement	Capacities	Load	Fuel Consumption	
FLEET 500	Perkins® 404D-22 EPA	4 Cylinder, 4 Cycle Water-Cooled Diesel	32.7 HP @ 1800 RPM 136 cu. in. (2.2L)	FUEL: 20gal. (76.0L) OIL: 8.45 qts (8.0L)	High Idle - No Load	0.42 gals/hr - 1.57 L/hr	
	Tier 4i	Engine, 12V Electric Start, Dry Type Air Cleaner, Fuel filter with Water Separator, Mechanical Governor	150 cu. III. (2.21)	RADIATOR COOL- ANT: 8.0 qts (7.6L)	Rated Output	1.18 gals/hr - 4.46 L/hr	

CUSTOMER ASSISTANCE POLICY

The business of Lincoln Electric is manufacturing and selling high quality welding equipment, automated welding systems, consumables, and cutting equipment. Our challenge is to meet the needs of our customers, who are experts in their fields, and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or technical information about their use of our products. Our employees respond to inquiries to the best of their ability based on information and specifications provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment, or provide engineering advice in relation to a specific situation. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or communications. Moreover, the provision of such information or technical information or tereate, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or technical information, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose or any other equivalent or similar warranty is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the definition of specifications, and the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change - This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.com for any updated information.