VELION[™]

ELECTRIC VEHICLE CHARGER





Pre-production model shown throughout. Actual production model may vary.

REDEFINING RELIABILITY OF EV CHARGING

With a proven track record of engineering rugged and dependable industrial equipment, Lincoln Electric is delivering the next generation of electric vehicle chargers with the Velion™ EV charger. Designed with industrial-grade components, the Velion platform delivers fast charging speeds with unparalleled reliability for the ultimate performance and uptime.

Charging Type »

DC Fast Charging

DC Output Voltage »

200-1000V DC

DC Output Current »

Up to 300A

DC Output Power »

Up to 150kW

Input Voltage »

460VAC +/- 10% (60Hz), 3-Phase, Protective Earth (UL Model)



TECHNICAL SPECIFICATIONS*

| Charging Station | |
|--------------------------|--|
| Charging Type | Level 3, DC Fast Charging |
| Input Voltage | 460VAC +/- 10% (60Hz), 3-Phase, Protective Earth (UL Model) |
| Input Current | 200A |
| DC Output Voltage | 200-1000V DC |
| Output Current | up to 300A |
| DC Output Power (max) | 150kW |
| Efficiency (full-load) | >95% |
| Power Factor (full-load) | > .95 |
| THDi | < 4.5% |
| IP Rating | IP-54 (NEMA 3R) |
| IK Rating | IK08 |
| Operating Temperature | -35 deg C to +50 deg C |
| Humidity | 20 - 95% Rh non-condensing |
| Mounting | Free Standing Cabinet |
| Dimensions | 36 x 24 x 72 (914 x 609 x 1828 mm) |
| Weight | 750 lbs. (340.2 kg) |

| Pedestal | |
|--------------------------------|---|
| Outlet Type | Single CCS Cable |
| Network Connection | GSM/3G/4G modem;10/100 Base-T Ethernet |
| Communication | OCPP 2.0.1 and 1.6 |
| Authentication/Payment | RFID/Credit card reader/App |
| User Interface | 15 in. LCD high-contrast touchscreen |
| IP Rating | IP-54 (NEMA 3-R) |
| IK Rating | IK08 |
| Operating Temperature | -35 deg C to +50 deg C |
| Humidity | 20 - 95% Rh non-condensing |
| Mounting | Free Standing Cabinet |
| Cable Length | 12 ft. (3.7 m) |
| Dimensions | 18 x 18 x 78 (457 x 457 x 1981 mm) |
| Weight | 150 lbs. (3810 kg) |
| System Certification Standards | |
| Charging System | UL2202, UL2231-1, -2, SAE J1772, SAE J2894 |
| Communication to the EV | DIN 70121, ISO15118-2/-3, ISO15118-20, |

CUSTOMER ASSISTANCE POLICY

The business of Lincoln Electric is manufacturing and selling high quality welding equipment, automated welding systems, consumables, and cutting equipment. Our challenge is to meet the needs of our customers, who are experts in their fields, and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or technical information about their use of our products. Our employees respond to inquiries to the best of their ability based on information and specifications provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment, or to provide engineering advice in relation to a specific situation. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or communications.

Moreover, the provision of such information or technical information does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose or any other equivalent or similar warranty is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the definition of specifications, and the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

^{*}Product specifications and features are subject to change. Confirm specification prior to purchase.