



LABELS

- ▲ SUPPLY VOLTAGE NET
- POWER SUPPLY SOURCE POINT
- ▽ COMMON CONNECTION

GENERAL INFORMATION

ELECTRICAL SYMBOLS PER E1537
 ALL DIODES 1AMP UNLESS OTHERWISE STATED
 ALL RESISTORS 1/2W UNLESS OTHERWISE STATED
 ALL CAPACITORS IN UF UNLESS OTHERWISE STATED

LAST NO. USED:

- R-34
- C-12
- D-14
- Q-14
- X-2

L11175

UNLESS OTHERWISE SPECIFIED TOLERANCE ON HOLE SIZES ARE E2008 ON 3 PLACE DECIMALS IS ±.02 ON ALL ANGLES IS ±.2 OF A DEGREE MATERIAL TOLERANCE IS TO AGREE WITH PUBLISHED STANDARDS.

THIS SHEET CONTAINS PROPRIETARY INFORMATION OWNED BY THE LINCOLN ELECTRIC CO. AND IS NOT TO BE REPRODUCED, DISCLOSED OR USED WITHOUT THE EXPRESS PERMISSION OF THE LINCOLN ELECTRIC CO.

THE LINCOLN ELECTRIC CO. EQUIP. RANGER 8 PLUS DIESEL (CSU) SOLENOID DRIVER PCB SCHEMATIC & BOARD REF. SCALE NONE DATE 2-22-99 CHK. D.J.S. MR. SUPP996

NO. L11175