

WANT TO BE VERSATILE WITH YOUR PIGTAIL OFFERING?

Flexible hose are used to transfer compressed and liquefied gases. They are available in various lengths and end fitting in either all stainless steel construction or stainless steel lined with PTFE

- Stainless Steel PTFE Lined
- Single Braided
- Smooth PTFE Inner Core
- Rated 3000 PSI
- Not recommended for hydrogen, helium and oxygen



Liquid Cryogenic

- Stainless Steel with Armored Jacket
- Standard lengths 4ft and 6ft
- Rated 1150 PSI
- Oxygen Cleaned



FEATURES

- All metal to metal
- Stainless steel lined with armor jacketed
- Safer than teflon lined braided pigtails
- Rated 3,850 PSI
- Oxygen Cleaned
- Helium and Hydrogen Diffusion Resistant

1st Order Pigtail Length

- All pigtails below are a 1/4" female by 1/4" male

9007826 - 24" Pigtail

9007827 - 36" Pigtail

9007828 - 72" Pigtail

9007829 - 120" Pigtail

*other size available on request

2nd Order CGA Assembly

Every CGA comes with integrated check valves to prevent reverse flow

- All CGA's are chrome plated
- Assembly comes with stem/nut/check valve
- Allows versatility to connect CGA's to Pigtails at a moments notice while carrying less stock

9030191 - CGA 590 (Ind. Air)

9030189 - CGA 580 (Nitrogen)

9030183 - CGA 540 (Oxygen)

9030186 - CGA 510 (Acetylene)

9030181 - CGA 350 (Hydrogen)

9030250 - CGA 320 (Carbon Dioxide)

*other CGA's available on request