

# RANGER® ENGINE-DRIVEN WELDER/GENERATORS

Select the Ranger® Model **That's Right for You**



RANGER® 225



RANGER® 250 GXT



RANGER® 260MPX™



RANGER® 305



RANGER® 330MPX™

PART NUMBER	K2857-1	K2382-4	K3458-1	K1726-5 - RANGER® 305 G K3928-1 - RANGER® 305 G EFI K2937-1 - RANGER® 305 LPG	K3459-1 - RANGER® 330MPX™ K4779-1 - RANGER® 330MPX™ EFI
TECHNOLOGY	Reactor Technology	Reactor Technology	Chopper Technology®	Chopper Technology®	Chopper Technology®
KEY REASON TO BUY	DC Stick Welding; Low Price	AC/DC Stick Welding; Excellent AC TIG	Smallest machine in its class with superior DC multi-process welding performance	Superior DC Multi-Process Welding	Smallest machine in its class with advanced capabilities and superior DC multi-process welding & gouging performance
ARC PERFORMANCE	<ul style="list-style-type: none"> <li>General purpose DC stick welding up to 225 amps</li> <li>Basic CV wire welding up to 200 amps</li> </ul>	<ul style="list-style-type: none"> <li>General purpose AC &amp; DC stick welding up to 250 amps</li> <li>Basic CV wire welding up to 250 amps</li> <li>Excellent AC TIG welding (with Optional TIG Module)</li> </ul>	<ul style="list-style-type: none"> <li>Superior multi-process DC arc performance up to 260 amps</li> <li>Excellent CC &amp; CV wire welding performance</li> <li>Touch Start TIG® (DC) welding</li> </ul>	<ul style="list-style-type: none"> <li>Superior multi-process DC arc performance up to 300 amps</li> <li>Wire welding up to 5/64 in. diameter, 3/16 in. stick electrode.</li> <li>Touch Start TIG® (DC) welding.</li> <li>Excellent pipe welding capability</li> </ul>	<ul style="list-style-type: none"> <li>Superior gouging and multi-process DC arc performance up to 330 amps</li> <li>Wire welding up to 5/64 in. diameter, 1/4 in. stick electrode</li> <li>Touch Start TIG® (DC) welding</li> <li>Excellent pipe welding capability</li> <li>Aluminum pulse welding capability</li> </ul>
GENERATOR TYPE	AC generator power for tools, lights, plasma cutting, and AC TIG welding	AC generator power for tools, lights, plasma cutting	Clean AC generator power for small inverters, tools, electronics, lights, plasma cutting, & AC TIG welding.	AC generator power for tools, lights, plasma cutting, and AC TIG welding	Clean AC generator power for small inverters, tools, electronics, lights, plasma cutting, and AC TIG welding
ENGINE TYPE	Gasoline for maximum portability	Gasoline for maximum portability	Gasoline for maximum portability	Gasoline for maximum portability (K1726-5 & K3928-1) LPG when gasoline and diesel emissions are not acceptable. (K2937-1)	Gasoline for maximum portability
REMOTE CAPABILITY	Not available	Connection for remote weld output	Connection for remote weld output control and wire feeder control cable Scalable remote control for precise settings	Connection for remote weld output control and wire feeder control cable	Connection for remote weld output control and wire feeder control cable Scalable remote control for precise settings
SPECIAL FEATURES	Low price for limited budgets	Product also available with stainless steel case sides and roof Fuel Gauge with hour meter	Easy to use digital user-interface Crossline® capabilities Maintenance Screen for easy service Direct connect spool gun capability	Digital weld meters to read pre-set and actual output Fuel gauge with hour meter	Easy to use digital user-interface Crossline® capabilities Advanced arc characteristics for fine tuning Maintenance screen for service alerts

## TECHNICAL SPECIFICATIONS

RATED OUTPUT: AMPS, VOLTS, DUTY	225A DC CC, 25V, 40% 210A DC CC, 25V, 100% 200A DC CV, 20V, 100%	250A DC CC, 25V, 100% <b>250A AC CC, 25V, 100%</b> 250A DC CV, 25V, 100%	260A DC CC, 26V, 100% 253A DC CV, 25.6V, 100% 260A DC TIG, 20.4V, 100%	305A DC CC, 29V, 100% 300A DC Pipe, 29V, 100% 300A DC CV, 29V, 100% 250A DC TIG, 30V, 100%	330A DC CC, 28V, 100% 330A DC Pipe, 28V, 100% 312A DC CV, 29V, 100% 330A DC TIG, 23V, 100%
WELD PROCESSES	CC-Stick, Scratch Start TIG, CV-Wire	CC-Stick, Scratch Start TIG, CV-Wire	CC-Stick, Touch Start TIG®, CV-Wire	CC-Stick, Touch Start TIG®, CV-Wire, Pipe, Gouging	CC-Stick, Pulse Touch Start TIG®, CV-Wire, Pipe, Gouging
AC GENERATOR (SINGLE PHASE)	10,500 Watts Peak 9,000 Watts Continuous	11,000 Watts Peak <b>10,000 Watts Continuous</b>	10,000 Watts Peak 9,500 Watts Continuous	10,500 Watts Peak 9,500 Watts Continuous	11,500 Watts Peak 10,000 Watts Continuous
CASE DIMENSIONS (H x W x D)	30 x 21.5 x 42.3 in. (762 x 546 x 1073 mm) 36.2 in. (920 mm) to top of exhaust tube	30 x 21.5 x 42.3 in. (762 x 546 x 1073 mm) 36.2 in. (920 mm) to top of exhaust tube	<b>26 x 20 x 36 in. (660 x 508 x 914 mm)</b> <b>28.8 in. (711 mm) to top of exhaust tube</b> Galvanized base to increase the life of the machine and help prevent rusting	30 x 21.5 x 42.3 in. (762 x 546 x 1073 mm) 36.2 in. (920 mm) to top of exhaust tube	<b>26 x 20 x 36 in. (660 x 508 x 914 mm)</b> <b>28.8 in. (711 mm) to top of exhaust tube</b> Galvanized base to increase the life of the machine and help prevent rusting
ENGINE FUEL & CAPACITY	Gasoline (12 Gallon)	Gasoline (12 Gallon)	Gasoline (11 Gallon)	Gasoline (12 Gallon) (K1726-5 & K3928-1) LPG (Liquid Propane Gas)(K2937-1)	Gasoline (11 Gallon)
ENGINE BRAND & HP	23 HP Kohler®	23 HP Kohler®	23.5 HP Kohler®	23 HP Kohler®(K1726-5) 25 HP Kohler® EFI (Electronic Fuel Injection) (K3928-1) 25 HP Kohler® (K2937-1)	<b>25 HP Kohler® (K3459-1)</b> <b>25 HP Kohler® EFI (Electronic Fuel Injection) (K4779-1)</b>
PRODUCT WEIGHT	514 lb. (233 kg)	602 lb. (273 kg)	446 lb. (202 kg)	510 lb. (231 kg) (K1726-5 & K3928-1) 480 lb. (218 kg) (K2937-1)	446 lb. (202 kg)
NOISE AT RATED LOAD SOUND LEVEL SOUND POWER (LWA)	76.4 dBA at 23 ft. (7 m)	76.4 dBA at 23 ft. (7 m)	74.7 dBA at 23 ft. (7 m)	76.7 dBA at 23 ft. (7 m)	74.7 dBA at 23 ft. (7 m)

#### CUSTOMER ASSISTANCE POLICY

The business of Lincoln Electric is manufacturing and selling high quality welding equipment, automated welding systems, consumables, and cutting equipment. Our challenge is to meet the needs of our customers, who are experts in their fields, and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or technical information about their use of our products. Our employees respond to inquiries to the best of their ability based on information and specifications provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment, or to provide engineering advice in relation to a specific situation. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or communications. Moreover, the provision of such information or technical information does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or technical information, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose or any other equivalent or similar warranty is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the definition of specifications, and the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to [www.lincolnelectric.com](http://www.lincolnelectric.com) for any updated information.

**The Lincoln Electric Company**  
22801 St. Clair Avenue · Cleveland, OH · 44117-1199 · U.S.A.  
[www.lincolnelectric.com](http://www.lincolnelectric.com)