

62-5E

MODEL

1YR
WARRANTY

HEAVY DUTY CUTTING TORCH FOR USE WITH ALL FUEL GASES

MODEL SHOWN:
62-5E

DESCRIPTION

The Model 62-5E is a heavy duty straight cutting torch designed to use any fuel gas. The 62 is an industry standard that is less expensive to own and operate, and is safer to use. Its triangular tube design and brazed connections offer strength, safety and a long service life.

DETAILS

Capacity: 12"/304.8mm

Certifications: UL® listed

Mixer Type: Equal pressure

Warranty: 1 year

Duty: Heavy

Where Used: Fabrication, demolition, etc.

Lengths: 18", 21", 36"

Related Items: Flashback arrestors P/N: 4302202
Equipped with: FlashGuard® check valves

Featured in Harris Classic and HardHat™ Cutter Pac®



PART #	MODEL #	HEAD	DESCRIPTION		**TIP STYLES
			LENGTH*	WEIGHT	
1003350	62-5AE	70°	18" / 457.2mm	3 lbs. / 1.3607 kg.	6290
1003430	62-5E	90°	18" / 457.2mm	3 lbs. / 1.3607 kg.	6290 AC
1003464	62-5AEL	70°	21" / 533.4mm	3.1 lbs. / 1.4061 kg.	6290 NX
1003440	62-5EL	90°	21" / 533.4mm	3.1 lbs. / 1.4061 kg.	6290 NXP
1003351	62-5AEL	70°	36" / 914.4mm	3.8 lbs. / 1.7236 kg.	6290 NFF
1003441	62-5EL	90°	36" / 914.4mm	3.8 lbs. / 1.7236 kg.	Acetylene Specialty Tips

*Also available in other lengths as a special. **All tips fit all torches

62-5F

MODEL

1YR
WARRANTY

MAXIMUM PERFORMANCE WHEN USING ALTERNATE FUELS*

MODEL SHOWN:
62-5F

DESCRIPTION

The 62-5F is a heavy-duty straight cutting torch designed to give maximum performance using low-cost alternate fuel gases.* Our special "F" injector can produce the hottest flame possible at the lowest gas pressures, making it the safest, most efficient design in the industry.

DETAILS

Capacity: 12"/304.8mm

Mixer Type: Injector

Duty: Heavy

Lengths: 18", 21", 27", 36" & 48"***

Certifications: UL® listed

Where Used: Fabrication,

shipbuilding, maintenance, etc.

Related Items:
Flashback arrestor P/N: 4302202
Slitting skid P/N: QC1HZSTK5
70°/90° Skid P/N: QC1HZSTK2

Equipped with:
FlashGuard® check valves
Featured in Classic and HardHat™ Cutter Pac®



PART #	MODEL #	HEAD	DESCRIPTION		TIP STYLES
			LENGTH**	WEIGHT	
1003360	62-5AF	70°	18" / 457.2mm	3 lbs. / 1.3607 kg.	6290 NX 6290 NXP 6290 NFF Alternate Fuel Specialty Tips
1003450	62-5F	90°	18" / 457.2mm	3 lbs. / 1.3607 kg.	
1003460	62-5BF	180°	18" / 457.2mm	3 lbs. / 1.3607 kg.	
1003370	62-5AFL	70°	21" / 533.4mm	3.1 lbs. / 1.4061 kg.	
1003470	62-5FL	90°	21" / 533.4mm	3.1 lbs. / 1.4061 kg.	
1003400	62-5AFL	70°	36" / 914.4mm	3.8 lbs. / 1.7236 kg.	
1003480	62-5FL	90°	36" / 914.4mm	3.8 lbs. / 1.7236 kg.	
1003426	62-5BFL	180°	36" / 914.4mm	3.8 lbs. / 1.7236 kg.	
1003411	62-5AFL	70°	48" / 1219.2mm	4.4 lbs. / 1.9958 kg.	
1003481	62-5FL	90°	48" / 1219.2mm	4.4 lbs. / 1.9958 kg.	
1003421	62-5BFL	180°	48" / 1219.2mm	4.4 lbs. / 1.9958 kg.	

NOT FOR USE WITH ACETYLENE. *Propane or Propylene based fuels and natural gas. **Available in other lengths as a "special order."

The Harris Products Group
A Lincoln Electric Company
4501 Quality Place - Mason, OH 45040
Customer Service: 1.800.733.4043
Fax: 513.754.8778
www.harrisproductsgroup.com



052016



Turn to the SINGLE STAGE REGULATOR Pros