



TECHNICAL INFORMATION SHEET

SUPER COLD GALVIZ

APPLICATION:

Harris Super Cold Galviz is a zinc rich primer that offers a new outlook in rust proofing. This spray is a zinc powder, epoxy resin that provides good adhesion and coverage on ferrous metals. The primer is highly resistant to salt corrosion and water.

SUPER COLD GALVIZ USES

Super Cold Galviz is used to rust proof automobiles, trucks, boat bodies, boat docks, along with gutters and other building structures. Super Cold is used after the welding process to reapply rust proofing on steels. Rust proofing air conditioners, HVAC/R ducts, sump pumps, fan blades and so many more ferrous metals. Ideal of exterior and interior water tanks

PROCEDURE

- 1- Shake well before applying
- 2- Apply only to clean, dry surfaces
- 3- Spray from a distance of 10 inches
- 4- Move can with short dusting strokes
- 5- Apply multiple coats if needed.
- 6- Can be applied to damaged hot dipped surfaces
- 7- Air dry 10-15 minutes.

BENEFITS

When approved can be used in federally inspected meat and poultry plants. Provides a galvanic barrier equal to hot dip galvanizing. Shelf Life of two years, if stored at room temperature. Do not exceed 120 degrees Fahrenheit.

COVERAGE

One gallon covers 400 square feet at 0.0025 thickness

SPECIFICATION

Meets specifications MIL-P-26915A,
MIL-T-26433, MIL-P-21035, MIL-P-46105

SAFETY INFORMATION:

WARNING: PROTECT yourself and others. Read and understand this information. FUMES AND GASES can be hazardous to your health. HEAT RAYS, (infrared radiation) from flame or hot metal can injure eyes.

- Before use, read and understand the manufacturer's instructions, Safety Data Sheets (SDS), and your employer's safety practices.
- Keep your head away from fumes.
- Use enough ventilation, exhaust at the flame, or heat source, to keep fumes and gases from your breathing zone and the general area.
- Wear correct eye, ear, and body protection.
- See American National Standard Z49.1, *Safety in Welding, Cutting, and Allied Processes*, published by the American Welding Society, 8669 Doral Blvd., Doral, Florida 33166; OSHA Safety and Health Standards, available from the U.S. Government Office, Washington, DC 20402.

STATEMENT OF LIABILITY- DISCLAIMER

Any suggestion of product applications or results is given without representation or warranty, either expressed or implied. Without exception or limitation, there are no warranties of merchantability or of fitness for particular purpose or application. The user must fully evaluate every process and application in all aspects, including suitability, compliance with applicable law and non-infringement of the rights of others. The Harris Products Group and its affiliates shall have no liability in respect thereof.

THE HARRIS PRODUCTS GROUP

A LINCOLN ELECTRIC COMPANY

4501 Quality Place • Mason, OH 45040 U.S.A Tel: 513-754-2000 Fax: 513-754-6015

Additional information available at our web site: www.harrisproductsgroup.com