# **SUPRANOX 316L**

# **TOP FEATURES**

- Easy arc striking and restriking.
- Suitable for use with either AC [minimum OCV 50V] or DC positive.
- Efficiency 100%.

### CLASSIFICATION

AWS A5.4 E316L-17 EN ISO 3581-A E 19 12 3 L R 12

# **CURRENT TYPE**

AC, DC+

### **WELDING POSITIONS**

All positions

### **APPROVALS**

ABS	BV	DNV	RINA	ΤÜV	DB
+	+	+	+	+	+

# CHEMICAL COMPOSITION (WEIGHT %), TYPICAL, ALL WELD METAL

С	Mn	Si	Р	S	Cr	Ni	Mo	Ferrite
0.035	0.9	0.8	≤0.025	≤0.025	19.0	12.0	2.6	5-10

# MECHANICAL PROPERTIES, TYPICAL, ALL WELD METAL

	Condition*	0.2% Proof strength (MPa)	Tensile strength (MPa)	Elongation (%)	Impact ISO-V (J) +20°C
AWS A5.4	AW	not specified	≥490	≥30	not specified
EN ISO 3581-A	AW	≥320	≥510	≥25	not specified
Typical values	AW	460	580	43	68

<sup>\*</sup> AW = As welded

# **OUTPUT RANGE**

Diameter x Length (mm)	Current range (A)
1.6 x 300	20-40
2.0 x 300	30-60
2.5 x 300	55-80
3.2 x 350	70-110
4.0 x 350	120-140

# **PACKAGING AND AVAILABLE SIZES**

Diameter x Length (mm)	Packaging	Electrodes/pack	Net weight/pack (kg)	Item number
1.6 x 300	VPMD	250	1.8	W000375922
2.0 x 300	CBOX	310	3.6	W000375872
2.5 x 300	CBOX	190	3.5	W000375873
3.2 x 350	CBOX	120	4.3	W000375876
4.0 x 350	CBOX	80	4.2	W000375878
5.0 x 350	CBOX	50	4.2	W000375881



### **TEST RESULTS**

Test results for mechanical properties, deposit or electrode composition and diffusible hydrogen levels were obtained from a weld produced and tested according to prescribed standards, and should not be assumed to be the expected results in a particular application or weldment. Actual results will vary depending on many factors, including, but not limited to, weld procedure, plate chemistry and temperature, weldment design and fabrication methods. Users are cautioned to confirm by qualification testing, or other appropriate means, the suitability of any welding consumable and procedure before use in the intended application

Safety Data Sheets (SDS) are available here:



Subject to Change – The information is accurate to the best of our knowledge at the time of printing. Please refer to <a href="www.lincolnelectric.eu">www.lincolnelectric.eu</a> for any updated information.

