RANGER® 260MP

MULTI-PROCESS WELDER GENERATOR



Shown: Ranger 260MP (K5937-1)

More Output. Same Simple Control.

The Ranger® 260MP™ is a step up in welding output with remote capability for crews that need more flexibility without adding complexity. Straightforward controls and a single, glove-friendly knob keeps the focus on the work, not the machine.

Running cooler, quieter, and longer, its reduced-weight, balanced design enhances jobsite mobility. Consistent, dependable output ensures reliable power with seamless transitions between welding and generator use.

Designed for ease of maintenance, a rear engine layout now gives unmatched access to key service parts. All MPs come factory filled with 300-hour premium oil to maximize runtime and are equipped with an electric fuel pump for reliable fueling.

Processes »
MIG, Stick, Flux-Cored

Applications »
Construction
Farm
Maintenance & Repair
Service

Output »



Input »





Publication E6.633 | Issue Date 10/26
©Lincoln Global Inc. All Rights Reserved. All trademarks and registered trademarks are the property of their respective owners.
www.lincolnelectric.com

LINCOLN® ELECTRIC

KEY FEATURES


- **One-knob, glove-friendly control —** Faster setup with less adjustment on the job
- **High-quality multi-process welding —** 260 amps of consistent, reliable weld performance across applications
- **Clean generator power —** 10.5kW safely powers jobsite tools and equipment
- **Electronic choke —** Easier starting with less manual adjustment
- **Auto-idle —** Reduces noise and fuel use when welding demand drops
- **Low-noise operation —** Better for jobsite comfort and communication
- **GFCI-protected receptacles —** Added protection when powering jobsite tools
- **Remote control switch —** Added flexibility and mobility on the job

INDUSTRY-LEADING DESIGN

- **Reduced-weight, jobsite-mobile design —** Easier transport and handling on site
- **IP23S-rated enclosure —** Built for durability in tough outdoor conditions
- **Rear-engine layout —** Easier access to service points
- **Front-facing fuel gauge —** Quick, convenient fuel checks
- **Front battery access —** Faster battery service or replacement

KEY CONTROLS

1. Fuel / Hour / Output Enabled Meter
2. CC / CV switch
3. Engine Start Switch
4. Remote Control Switch
5. One-knob amperage control
6. 15 amp circuit breaker
7. 240 Volt AC receptacle
8. 120/240 Volt AC Full KVA receptacle
9. 50 amp circuit breaker for AC power
10. 20 amp circuit breaker AC power going to the 120V receptacles
11. GFCI protected 120 Volt AC receptacle
12. Ground Stud
13. 6-pin connection for remote capabilities
14. Output Studs
15. Battery Tray



RECOMMENDED ACCESSORIES

Product Name	Product Number
Stick Accessories	
Stick welding kit with electrode cable 20 foot #6, work cable 15ft #6, electrode holder, work clamp and helmet. 150 amp nominal rating	K875
EH-305HD Heavy Duty Electrode Holder	K909-7
EH-405HD Heavy Duty Electrode Holder	K909-8
General Accessories	
Ranger MP Nylon Cover	K6055-1
Work and power lead package (10 ft, 2/0) – Tweco male and ground clamp / Tweco male and lug	K1803-2
Work lead package (15 ft, 2/0) lug connector	K2150-1
Weld power cable - lug to lug (3/0) – 10 foot	K1842-10
Weld power cable - lug to lug (4/0) – 35 ft (2 cables per package)	K2163-35
Weld power cable – lug to lug (4/0) – 60 ft (2 cables per package)	K2163-60
Weld cable – Tweco Male to open end (2/0) – 10 ft	K2483-2
Weld cable – Tweco Male to open end (3/0) – 10 ft	K2483-3
Weld Cable – Tweco Male & Female (2/0) – 50 ft	K2485-2
Weld cable - Tweco Male & Female (3/0) – 50 ft	K2485-3
Weld Cable – Tweco Male to lug (3/0) - 50 ft	K2484-3
Insulated CT40FS Female Connector, straight	K2487-1
Tweco-Style Cam-Lock Adapter Plug for 2/0 Cable	K2946-1
Tweco Style Plug (male, 1/0 through 2/0)	K3416-70
Tweco Style Plug (male, 3/0 through 4/0)	K3416-90
Tweco Style Plug (female, 1/0 through 2/0)	K3417-70
Tweco Style Plug (female, 3/0 through 4/0)	K3417-90
Remote Output Control 6 pin, 25 foot	K857
Remote Output Control 6 pin, 100 foot	K857-1
Trailers and Undercarriages	
Small Two-Wheel Welder Trailer	K2635-1
Factory Undercarriage, pneumatic tires	K3589-5
Factory Undercarriage with Flat-Free Tires	K3589-6
All-Terrain Undercarriage, pneumatic tires	K3590-4
All-Terrain Undercarriage with Flat-Free Tires	K3590-5
Engine Accessories	
Rehlko 100 hour service kit	K3494-1
Spark Arrestor	K3679-1

PRODUCT SPECIFICATIONS

Product Name	Product Number	Weld Power			Generator Power			
		IEC rating @ 100%	Output Range	OCV Max	Power	Voltage (Single Phase)	14-50R Full kVA Receptacle	5-20 Receptacles
Ranger® 260MP	K5937-1	231A/29.2/100% CC/Stick 253A/26.7V/100% CV/Wire 260A/26V/100% (Non IEC Rating)	35-260A (CC) 15-30V (CV)	85VDC	10,500W (Peak) 9,500W (Continuous)	120/240V AC	40A @ 240VAC 40A @ 120V ea branch circuit	20A @ 120VAC total, GFCI protected

Engine (Make & Model)	Power	Displacement	Engine controls	Idle Speed	Fuel System	Fuel Capacity	Battery	Dimension (H x W x D) in (mm)	Weight lbs (kg)
Rehlko CH730	23.5 hp	725 cc (44 in^3)	Electronic choke, carburetor	2,500 RPM 3,600 RPM (High Idle Speed)	Gasoline with electric fuel pump, 10% maximum ethanol	11 gallon (42 l)	12V Group 26 500 CCA	26.4 x 20 x 36.4 (671 x 508 x 924) To Top of Exhaust Pipe: 33.1 (840)	426 (194)

CUSTOMER ASSISTANCE POLICY

The business of Lincoln Electric is manufacturing and selling high quality welding equipment, automated welding systems, consumables, cutting equipment and EV charging systems. Our challenge is to meet the needs of our customers, who are experts in their fields, and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or technical information about their use of our products. Our employees respond to inquiries to the best of their ability based on information and specifications provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment, or to provide engineering advice in relation to a specific situation or application. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or communications. Moreover, the provision of such information or technical information does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or technical information, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose or any other equivalent or similar warranty is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the definition of specifications, and the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

LINCOLN® ELECTRIC